

# Mass flow meter

**Publication number:** EP0691528 (A2)  
**Publication date:** 1996-01-10  
**Inventor(s):** VAN DER POL RONALD DIPL-ING [NL] +  
**Applicant(s):** KROHNE AG [CH] +  
**Classification:**  
- international: **G01F1/84; G01F1/76;** (IPC1-7); G01F1/84  
- European: G01F1/84  
**Application number:** EP19950109986 19950627  
**Priority number(s):** DE19944423168 19940704

## Also published as:


EP0691528 (A3)  
EP0691528 (B1)  
JP8170927 (A)  
DE4423168 (A1)

## Cited documents:

WO9322629 (A1)  
WO8802105 (A1)  
EP0272758 (A2)  
DE4327052 (A1)  
EP0212782 (A1)

## Abstract of EP 0691528 (A2)

The mass flow meter includes a control system (5), which contains a vibration generator (6) acting on a vibration producer (2) attached to the Coriolis tube (1) conveying the substance. Two vibration receivers (3,4) transmit measuring signals to a phase-difference detector (7) in the control system which determines the proportional phase difference between them in the Coriolis line. This information appears on a digital display (10). In this system the stimulation-generator (6) is adjustable so that the amplitude of the vibration at the Coriolis line may have an optimal value. A regulator (8) controls the time-averaged amplitude of the vibration generator (6). There is also an overload warning system (11) using a threshold comparator (12).



.....  
Data supplied from the **espacenet** database — Worldwide